



### Features

- Portable barcode label printer pos printer thermal driver
- Support Thermal Receipt Roll Paper & Label Paper
- Support paper width from 16mm to 82mm
- Support printer head pressure adjustment
- Support paper auto verify
- Automatic temperature control
- Easy paper-roll installation.
- Easy paper jam clearance.
- Easy maintenance



Print	Printing method	Thermal line printing
	Resolution	203dpi (8dots/mm)
	Print width	16mm~82mm
	Print speed	127mm/sec. (Max.); 101mm/sec. (Min.)
	Memory	DRAM: 2M ; FLASH: 2M
	Print head temperature sensor	Thermal sensitive resistance
	Print head position sensor	Micro switch
	Black mark sensor	Photoelectric sensor
	Interface	Parallel/RS232C+USB/LAN
Barcode font & Graphics	Barcode	CODE128, EAN128, ITF, CODE39, CODE93, EAN13,EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5,CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5,UPC-E, UPCE+2, UPC-E+5, CPOST, MSI, MSIC,PLESSEY, ITF14, EAN14
	Enlargement & rotation	1 to10 times Enlargement in both directions; 0°, 90°, 270°, 360° rotation
	Graphics	Black and white PCX and BMP files can be downloaded into FLASH and DRAM
Media	Media type	Continuous,sticker,fan-fold,etc.
	Media width	16mm~82mm
	Media diameter	Max.85mm
	Media core diameter	Min.25mm
	Paper off type	Tear off & peel off
Power	Input	24VDC, 2.5A
Environment condition	Work	5~45,20~80%RH
	Storage	- 40~55 ,=93%RH(40)
Physical dimension	Dimension	220*150*150mm( L*W*H)
	Weight	2.68KG