



## Features

- ▶ Mini size, double injection molding and rubber protection around, durable enough for anti-dropping.
- ▶ Non-slip design (salient points on the rubber of the two sides)
- ▶ Exclusive power indication light
- ▶ Support USB, power adapter or mobile power charging
- ▶ Has standby mode to save power
- ▶ Provide SDK for IOS and Android

Color	Orange/Gray
Printing way	Thermal Line Printing
Paper width	80mm
Printing width	72 mm
Resolution	203dpi(8 dot/mm)
Printing speed	75 mm/s (max)
Dot /line	576 dots/line
Print Font	ASCII Font A: 12×24/ASCII Font B: 9×17/Chinese: 24×24
Characters per Line	Font A: 48/Font B: 64/Chinese: 24
Rolling paper Diameter	φ 40(max)X80mm
Paper feeding method	Easy paper loading
Barcode type	CODE39/EAN-13/EAN- 8/CODABAR/CODE93/ITF /QR/PDF417
MCBF	5 Million Lines
Print head lifespan	50 km
Interface	Bluetooth(BT4.0&BLE)/WiFi/USB/RS232
Paper out alarm	Support
Printing Command	ESC/POS
Power Supply	USB/Power adapter/mobile power charging
Power alarm	Battery need to be charged or changed when battery light turns off and red light turns on
Dimension (LxWxH)	113×103×45(mm)
Weight	335g (including the paper roll and battery)

Battery	2000 mAh rechargeable li-ion battery
	lifespan is more than 500 times
	Continuously working for 3 hours or 100m
	4-6 hours charging time

Environment parameters	Working temperature: -10? ~ 50?
	Working humidity: 20% ~ 85%
	Storing temperature : -20? ~ 70?
	Storing humidity: 5% ~ 95%

